



- GENERAL SPECIFICATIONS:
- ENCLOSURE - INDOOR/OUTDOOR CONSTRUCTION
 - CODE GAUGE STEEL PER APPLICABLE U/L, NEMA AND ANSI STANDARDS.
 - FINISH - ANSI 61 LIGHT GRAY
 - FUSE RATING - 10E-200E CURRENT LIMITING
 - INTEGRATED SWITCH/FUSE RATING - 63K SYM AMPERES U/L LISTED ASSEMBLY
 - SWITCH - 5.5KV MAXIMUM VOLTAGE
 - 200AMPS CONTINUOUS
 - 12.5K AMPS SHORT TIME(1.0 SEC)
 - 20K AMPS MOMENTARY
 - 20K AMPS FAULT CLOSING
 - 19K VOLTS LOW FREQUENCY WITHSTAND
 - 60K VOLTS IMPULSE WITHSTAND

BILL OF MATERIAL

ITEM	QTY	MFG.	CATALOG NO.	DESCRIPTION
1	1	SQ-D	HVM030502UL	200A, 5KV, 3-POLE SWITCH
1a	1	SQ-D	HVM0FK5-2	LIVE PARTS HARDWARE W/MTG BASE ASSEMBLY
2	3	MERSEN	A055F1DORO-XXXE	5KV, XXXE, CURRENT LIMITING FUSES
		SHAWMUT		(TO BE DETERMINED BY CUSTOMER)
3				
4				
5				

SCALE: 1"=1'

PCI
POWER CONTROLS, INC.

7400 BANDINI BLVD.
COMMERCE, CA. 90040
(800) 777-6622

DWN BY: MC
DATE: 08-16-16

WORK ORDER
XXXX

SOLD TO: ROMAC
JOB NAME: STOCK

TITLE:
200A, 5KV, 3PH, 3W LOAD INTERRUPTER SWITCH
INDOOR NEMA 1 & OUTDOOR NEMA 3R CONSTRUCTION

DRAWING NUMBER:
41-PCLI0502

REV